trivum CW130-S

Article-Number: 700013

EAN: 4260393850385

 \bigcirc

trivum single speaker for ceiling and wall mounting was developed in order to achieve the highest possible efficiency factor combined with the clearest audio reproduction. Distortions and sound colorations are reduced to an absolute minimum resulting in a clear intelligibility.

The single loudspeaker CW130-S is the perfect complement to the trivum multiroom systems.







Power

The CW130-S has a high, short-term peak power capacity of 2x 75 watt.



Efficiency factor

With its efficiency factor of 90 dB/W the CW130-S belongs to the market leaders in this size.



Impedance

A high impedance of 8 ohm is very important for flush mount speakers since they are usually connected to long cables.



Tweeter Level

The CW130-S has a tweeter level adjustment in order to adjust the sound to spacial and acoustical prerequisites.



Reproduction quality

The loudspeakers impress with clear reproduction and audibility due to the minimization of distortions ans sound intelligibility.



Grills

The included round and square grills can be exchanged anytime without the need to remove or exchange the speakers.

Installation

Fast and easy installation in 3 steps:

- Cut out mounting hole
- · Install cable and speaker
- Install the grill

Stereo

The CW130-S is a stereo speaker. Therefor, it has two separate voice coils for the bass and two separate tweeters with likewise two audio crossovers.





As of 08/2017. Misprints, errors and changes reserved without prior notice.

TTIVUM () smart multiroom

1470 g

Function

Speaker for	ceiling and	wall mounting.
-------------	-------------	----------------


|--|


Tweeter diameter	2x 20 mm silk dome
Tweeter mounting	-
Tweeter level switch	yes, 0 dB & -3 dB
Woofer diameter	130 mm
Impedance	2 x 8 Ω
Power capacity (peak)	2 x 75 W
Sensitivity	90 dB/W
Response -3 dB	61 Hz–20 kHz

 $\widehat{\Box}$

Net weight

Grills 200 mm Round grill (diameter) Square grill 200 x 200 mm Magnetic grill fixing yes Dimensions 2 mm t, d_1 195 mm Ultra thin bezel 1 mm Ultra shallow grill 3.5 mm Installation depth (t_2) 83 mm Mounting diameter (d_2) 178 mm





SPL vs Freq							
	<i>~</i> ~	~~~	~~	~~~~	~~~		
8 38 38 39							
AD	100 200	800 16	26	6K 8	111		

KNX

